### Sonesse 30 WireFree Li-ion RTS

PRODUCT SPECIFICATIONS

# Designed for silence and simplicity

The new silent motor for residential medium to large blinds, powered by a built-in rechargeable battery.





## Lithium-ion 🕇

Embedded battery motor:

- All-in-one
- Aesthetic
- Compact and light
- Higher energy and density
- Battery power indicator
- Rapid recharging

Adjustable speed

From 10 to 28 rpm.



**Built-in battery motor** Powered by a compact and light lithium-ion battery.



SOFT START

AND

SOFT STOP

**"my" favourite** In one click move the blind to your favourite position.

Soft start and

soft stop



Wirefree For quicker installation.

Compatible with Mod/Var functions



**Information feedback** Low battery indicator on the controller interface and easy re-setting.

e somfy



Thin head White and thin round head for discrete blending.



ADJUSTABLE

SPEED

Slats tilting





# Sonesse 30 WireFree Li-ion RTS

### **BENEFITS FOR PROFESSIONALS**

### **Easy Integration**

- Suitable for tubes diameter 30 mm or more
- Fits either steel or aluminium tube
- Aesthetic white and thin motor head
- Attached external antenna
- No external battery tube
- Delivery mode

### **Easy Installation**

- No wiring
- No need to have electrical knowledge
- Sleep mode

### Quick setting

### • Program button

• Up and down end limits set via transmitter

### **Reliability and profitability**

- Safe protocol
- · Somfy brand awareness and quality

те	сци		DAT	Λ
1 6		IILAL		
				1.1

### **BENEFITS FOR END USERS**

### Daily convenience and comfort

- Quiet operation
- Move your blinds effortlessly and remotely thanks to radio control
- · Move your blind in one click to your favourite "my" position
- Smooth motion with adjustable speed

### Aesthetic integration


- Quick and clean installation with no damage to walls
- · White and thin head
- No electrical wires or cords, free from danger of strangling

### Easy use and maintenance

- Rechargeable battery (only recharge once per year)
- Low battery LED indicator

### **COMPATIBLE END PRODUCTS**

### For interior applications only.





Sheer

PERFORMANCES

\* Using CTS40

Voltage Supply	12V DC	
Index Protecting Rating	IP 30 (for indoor use only)	
Limit Switch Type	Electronic	
Temperature Working Range	0°C to 60°C	
Temperature Storage Range	-20°C to 60°C	
Insulation Class	Class III	
Antenna	15 cm wire length must not be cut or lengthened. For greatest RF range, it must not be exposed and should not come in contact with metal surfaces. RF wire may need to be repositioned for optimal performance.	

I ENI ONMANCES		
Nominal Torque	2 Nm	
Nominal Speed	20 rpm (Sonesse noise performance)	
Adjustable Speed	10-28 by increment of 1-2 rpm	
Sound Level	44 dBa (at nominal speed)	
Radio Protocol	RTS	
Radio Frequency	433.42 MHz	
Battery Lifetime	Nominal 10 months	
Power Supply	Li-ion embedded battery	
Low Battery Indicator	LED	
Item Number	1003128	


.3 in. (7.6 mm)

### DIMENSIONS

L (mm): 590 mm + Plug end Tube min Ø (int): 28.8 mm

# 23.69 in. (601.7mm)

Motor Charging Cable (attached) 10 in. (254 mm) Plug



### PARTS AND ACCESSORIES

Li-ion charger has to be ordered separately		Accessories a	Accessories available:	
9020673	Li-ion charger extension cable 96/2.4 m	9021018	Sonesse 30 WF Acmeda Sys45 Crown and drive	
9020811	Li-ion charger 30 series AUS	9021036	Sonesse 30 WF Acmeda Sys45 Heavy Crown and drive	
		9021037	Sonesse 30 WF HD Qantam Crown and drive	
		9020699	Sonesse 30 WF HD 37 mm Crown and drive	
		9020674	Sonesse 30 WF Rollease 1.5/32 mm Crown and drive	
		9020675	Sonesse 30 WF Louvolite 40 mm Crown and drive	
		9020676	Sonesse 30 WF to 400s adapter kit	

SOMFY Pty Limited – ABN 77 003 917 244 – 20/38-46 South St, Rydalmere NSW 2116 – T +61 (0)2 8845 7200 – somfy.au@somfy.com

